



WEVER & DUCRÉ  
LIGHTING

# TAPE 8.0

722474D5

## GENERAL

Floor  
Surface  
Dark Grey Texture  
IP65  
Exterior  
Indirect 10 lm  
Direct 410 lm  
Total 420 lm

## LED

3000 K  
CRI 90  
L90 / 50000 h  
3-step binning

## OPTICAL

Wide Flood

## PHYSICAL

Length 180 mm  
Width 60 mm  
Height 800 mm  
3.1 kg


## ELECTRICAL

phase-cut dim  
220 - 240 V  
Total connected power 8 W  
PC1  
0.3 m


Project  
Type  
Notes  
Quantity  
Date



IP65



## LIGHT DISTRIBUTION





WEVER & DUCRÉ  
LIGHTING

# TAPE 8.0

722474D5

Project

Type

Notes

Quantity

Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF <sup>a</sup>	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF <sup>a</sup>	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## GROUND SPIKE

### Ground Spike

TYPE	L · W · H (MM)	ORDERCODE
TAPE   PACE	58-70-356	9 0 0 1 3 1 0 2