# **TRAIN** 1.0

#### 306668B3

#### GENERAL

Wall
Surface
Jet Black
IP20
Interior
385 lm
9005 <sup>a</sup>

#### LED

2700 K
CRI 90
L70 / 50000 h
3-step binning

#### OPTICAL

Beam angle 38°

### PHYSICAL


Length 50 mm
Width 50 mm
Height 85 mm
0.24 kg

### ELECTRICAL

phase-cut dim
220 - 240 V
Total connected power 7.9 W
PC1
0.3 m
<sup>a</sup> BAL Palette colors may deviate slightly due

<sup>a</sup> RAL Palette colors may deviate slightly due to production conditions.










# LIGHT DISTRIBUTION



306668B301 The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/-10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply. © Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com WEVER & DUCRÉ

# **TRAIN** 1.0

306668B3

## CONE DIAGRAM

38°

E0° (lx)	ø (m)
786	0.69
197	1.38
87	2.06
49	2.75
31	3.44
	786 197 87 49

306668B301 The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/-10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/-150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of Wever & Ducré BVBA apply. Wever & Ducré BVBA · Spinnerijstraat 99/21 · 8500 Kortrijk · Belgium · www.weverducre.com