



WEVER & DUCRÉ
LIGHTING

TUBE WALL 2.0 LED

711264B5

GENERAL

Wall
Surface
Jet Black
IP65
Exterior
Indirect 390 lm
Direct 430 lm
Total 820 lm
9005^a

LED

3000 K
CRI 90
L90 / 50000 h
3-step binning

OPTICAL

Flood

PHYSICAL

Diameter 80 mm
Height 152 mm
0.74 kg

ELECTRICAL


phase-cut dim
220 - 240 V
Total connected power 16 W
PC1
0.3 m

^a RAL Palette colors may deviate slightly due to production conditions.


Project
Type
Notes
Quantity
Date



IP65



LIGHT DISTRIBUTION





WEVER & DUCRÉ
LIGHTING

TUBE WALL 2.0 LED

711264B5

Project _____

Type _____

Notes _____

Quantity _____

Date _____

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.98	0.98	0.97	0.97
LSF	1	1	1	1	1

MF	$LMF \times RSMF \times LLMF \times LSF$	RSMF ^a	Room Surface Maintenance Factor
MF	Maintenance Factor	LLMF	Lamp Lumens Maintenance Factor
LMF ^a	Luminaire Maintenance Factor	LSF	Lamp Survival Faktor

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.