

CEILING LED LUMINAIRE

POWER SUPPLY: 230 V AC/ 50 - 60 Hz

LIGHT SOURCE: LED

POWER: 2x20 W

LUMINOUS FLUX: 2 x 2110 Lm

BEAM ANGLE: 40°

DIMMING: Non Dimm / DALI Dimm

CRI: 90

PROTECTION: IP20

DIMENSIONS: 339 x 179 x 163 mm

AMBIENT TEMPERATURE: -15 to +40°C

COLOUR TEMPERATURE: 3000 / 4000 K

MATERIAL: aluminium, wood, steel, PMMA

APPLICATION: interior



TRILUM


TRILUM - Sladovnicka 28 - 971 01 Trnava - Slovakia
www.trilum.eu - trilum@trilum.eu - 00421 948 708 008

DATA SHEET


woodLED duoSPOT



LIGHT DISTRIBUTION



DIMENSIONS



OPTIONAL VENEERING



ORDER CODES

woodLED duo SPOT, 3000K, Non Dimm, maple - 024-M200934-00
woodLED duo SPOT, 3000K, Non Dimm, oak - 024-D200934-00
woodLED duo SPOT, 3000K, Non Dimm, cherry - 024-C200934-00
woodLED duo SPOT, 3000K, Non Dimm, walnut - 024-W200934-00
woodLED duo SPOT, 3000K, Non Dimm, palisander - 024-P200934-00
woodLED duo SPOT, 4000K, Non Dimm, maple - 024-M200944-00
woodLED duo SPOT, 4000K, Non Dimm, oak - 024-D200944-00
woodLED duo SPOT, 4000K, Non Dimm, cherry - 024-C200944-00
woodLED duo SPOT, 4000K, Non Dimm, walnut - 024-W200944-00
woodLED duo SPOT, 4000K, Non Dimm, palisander - 024-P200944-00
woodLED duo SPOT, 3000K, DALI, maple - 024-M200934-DA
woodLED duo SPOT, 3000K, DALI, oak - 024-D200934-DA
woodLED duo SPOT, 3000K, DALI, cherry - 024-C200934-DA
woodLED duo SPOT, 3000K, DALI, walnut - 024-W200934-DA
woodLED duo SPOT, 3000K, DALI, palisander - 024-P200934-DA
woodLED duo SPOT, 4000K, DALI, maple - 024-M200944-DA
woodLED duo SPOT, 4000K, DALI, oak - 024-D200944-DA
woodLED duo SPOT, 4000K, DALI, cherry - 024-C200944-DA
woodLED duo SPOT, 4000K, DALI, walnut - 024-W200944-DA
woodLED duo SPOT, 4000K, DALI, palisander - 024-P200944-DA