

SUSPENSION LED LUMINAIRE

POWER SUPPLY: 230 V AC / 50 - 60 Hz

LIGHT SOURCE: Samsung 2835 LED

POWER: 50 W

LUMINOUS FLUX: 4460 lm / 4000 K

BEAM ANGLE: 120°

DIMMING: PUSH DIMM / DALI

CRI: 90

PROTECTION: IP20

DIMENSIONS: Ø 590 x 104 mm

Rope length max. 2000 mm

AMBIENT TEMPERATURE: -15 to +40°C

COLOUR TEMPERATURE: 3000 / 4000 K

WEIGHT: 8 kg

MATERIAL: aluminium, wood, steel, PMMA

APPLICATION: interior



TRILUM


TRILUM - Sladovnička 28 - 971 01 Tmava - Slovakia
www.trilum.eu - trilum@trilum.eu - 00421 948 708 008

DATA SHEET


woodLED ROUND Hang 600



LIGHT DISTRIBUTION



DIMENSIONS



OPTIONAL VENEERING



ORDER CODES

woodLED ROUND 600, 3000K, DALI - maple+KIT - 004-MM0H83S-DA+KIT
woodLED ROUND 600, 3000K, DALI - oak+KIT - 004-DD0H83S-DA+KIT
woodLED ROUND 600, 3000K, DALI - cherry+KIT - 004-CC0H83S-DA+KIT
woodLED ROUND 600, 3000K, DALI - walnut+KIT - 004-WW0H83S-DA+KIT
woodLED ROUND 600, 3000K, DALI - palisander+KIT - 004-PP0H83S-DA+KIT
woodLED ROUND 600, 4000K, DALI - maple - 004-MM0H84S-DA+KIT
woodLED ROUND 600, 4000K, DALI - oak+KIT - 004-DD0H84S-DA+KIT
woodLED ROUND 600, 4000K, DALI - cherry+KIT - 004-CC0H84S-DA+KIT
woodLED ROUND 600, 4000K, DALI - walnut - 004-WW0H84S-DA+KIT
woodLED ROUND 600, 4000K, DALI - palisander+KIT - 004-PP0H84S-DA+KIT