

RECESSED LED LUMINAIRE

POWER SUPPLY: 230 V AC / 50 – 60 Hz

LIGHT SOURCE: Samsung 2835 LED

POWER: 155 W

LUMINOUS FLUX: 15300 lm / 4000 K

BEAM ANGLE: 120°

DIMMING: PUSH DIMM / DALI

CRI: 90

PROTECTION: IP20

DIMENSIONS: Ø 1174 x 150 mm

AMBIENT TEMPERATURE: -15 to +40°C

COLOUR TEMPERATURE: 3000 / 4000 K

WEIGHT: 18 kg

MATERIAL: aluminium, wood, steel, PMMA

APPLICATION: interior



TRILUM


TRILUM - Sladovnícka 28 - 971 01 Trnava - Slovakia
www.trilum.eu - trilum@trilum.eu - 00421 948 708 008

DATA SHEET


woodLED ROUND Tilt 1200



LIGHT DISTRIBUTION



DIMENSIONS



OPTIONAL VENEERING



ORDER CODES

- woodLED ROUND 1200, 3000K, DALI- maple+KIT - 006-MM0T83S-DA+KIT
- woodLED ROUND 1200, 3000K, DALI - oak+KIT - 006-DD0T83S-DA+KIT
- woodLED ROUND 1200, 3000K, DALI - cherry+KIT - 006-CC0T83S-DA+KIT
- woodLED ROUND 1200, 3000K, DALI - walnut+KIT - 006-WW0T83S-DA+KIT
- woodLED ROUND 1200, 3000K, DALI-palisander+KIT - 006-PP0T83S-DA+KIT
- woodLED ROUND 1200, 4000K, DALI - maple+KIT - 006-MM0T84S-DA+KIT
- woodLED ROUND 1200, 4000K, DALI - oak+KIT - 006-DD0T84S-DA+KIT
- woodLED ROUND 1200, 4000K, DALI - cherry+KIT - 006-CC0T84S-DA+KIT
- woodLED ROUND 1200, 4000K, DALI - walnut +KIT - 006-WW0T84S-DA+KIT
- woodLED ROUND 1200, 4000K, DALI-palisander+KIT - 006-PP0T84S-DA+KIT