

# CEILING LED LUMINAIRE

POWER SUPPLY: 230 V AC/ 50 - 60 Hz

LIGHT SOURCE: LED

POWER: 20 W

LUMINOUS FLUX: 2110 Lm

BEAM ANGLE: 40°

DIMMING: Non Dimm / DALI Dimm

CRI: 90

PROTECTION: IP20

DIMENSIONS: 179 x 179 x 163 mm

AMBIENT TEMPERATURE: -15 to +40°C

COLOUR TEMPERATURE: 3000 / 4000 K

MATERIAL: aluminium, wood, steel, PMMA

APPLICATION: interior



## TRILUM


TRILUM - Sladovnícka 28 - 971 01 Tmava - Slovakia  
www.trilum.eu - trilum@trilum.eu - 00421 948 708 008

# DATA SHEET


woodLED single SPOT



## LIGHT DISTRIBUTION



## DIMENSIONS



## OPTIONAL VENEERING



## ORDER CODES

- woodLED single SPOT, 3000K, Non Dimm, maple - 023-M200934-00
- woodLED single SPOT, 3000K, Non Dimm, oak - 023-D200934-00
- woodLED single SPOT, 3000K, Non Dimm, cherry - 023-C200934-00
- woodLED single SPOT, 3000K, Non Dimm, walnut - 023-W200934-00
- woodLED single SPOT, 3000K, Non Dimm, palisander - 023-P200934-00
- woodLED single SPOT, 4000K, Non Dimm, maple - 023-M200944-00
- woodLED single SPOT, 4000K, Non Dimm, oak - 023-D200944-00
- woodLED single SPOT, 4000K, Non Dimm, cherry - 023-C200944-00
- woodLED single SPOT, 4000K, Non Dimm, walnut - 023-W200944-00
- woodLED single SPOT, 4000K, Non Dimm, palisander - 023-P200944-00
- woodLED single SPOT, 3000K, DALI, maple - 023-M200934-DA
- woodLED single SPOT, 3000K, DALI, oak - 023-D200934-DA
- woodLED single SPOT, 3000K, DALI, cherry - 023-C200934-DA
- woodLED single SPOT, 3000K, DALI, walnut - 023-W200934-DA
- woodLED single SPOT, 3000K, DALI, palisander - 023-P200934-DA
- woodLED single SPOT, 4000K, DALI, maple - 023-M200944-DA
- woodLED single SPOT, 4000K, DALI, oak - 023-D200944-DA
- woodLED single SPOT, 4000K, DALI, cherry - 023-C200944-DA
- woodLED single SPOT, 4000K, DALI, walnut - 023-W200944-DA
- woodLED single SPOT, 4000K, DALI, palisander - 023-P200944-DA