

CEILING LED LUMINAIRE

POWER SUPPLY: 230 V AC/ 50 - 60 Hz

LIGHT SOURCE: LED

POWER: 8 W

LUMINOUS FLUX: 650 Lm

BEAM ANGLE: 40°

DIMMING: Non Dimm / DALI Dimm

CRI: 90

PROTECTION: IP20

DIMENSIONS: 118 x 118 x 135 mm

AMBIENT TEMPERATURE: -15 to +40°C

COLOUR TEMPERATURE: 3000 / 4000 K

MATERIAL: aluminium, wood, steel, PMMA

APPLICATION: interior




TRILUM


TRILUM - Sladovnicka 28 - 971 01 Trnava - Slovakia
www.trilum.eu - trilum@trilum.eu - 00421 948 708 008

DATA SHEET


woodLED singleSPOT mini



LIGHT DISTRIBUTION



DIMENSIONS



OPTIONAL VENEERING



ORDER CODES

- woodLED single SPOT mini, 3000K, Non Dimm, maple - 015-M200834-00
- woodLED single SPOT mini, 3000K, Non Dimm, oak - 015-D200834-00
- woodLED single SPOT mini, 3000K, Non Dimm, cherry - 015-C200834-00
- woodLED single SPOT mini, 3000K, Non Dimm, walnut - 015-W200834-00
- woodLED single SPOT mini, 3000K, Non Dimm, palisander - 015-P200834-00
- woodLED single SPOT mini, 4000K, Non Dimm, maple - 015-M200844-00
- woodLED single SPOT mini, 4000K, Non Dimm, oak - 015-D200844-00
- woodLED single SPOT mini, 4000K, Non Dimm, cherry - 015-C200844-00
- woodLED single SPOT mini, 4000K, Non Dimm, walnut - 015-W200844-00
- woodLED single SPOT mini, 4000K, Non Dimm, palisander - 015-P200844-00
- woodLED single SPOT mini, 3000K, DALI, maple - 015-M200834-DA
- woodLED single SPOT mini, 3000K, DALI, oak - 015-D200834-DA
- woodLED single SPOT mini, 3000K, DALI, cherry - 015-C200834-DA
- woodLED single SPOT mini, 3000K, DALI, walnut - 015-W200834-DA
- woodLED single SPOT mini, 3000K, DALI, palisander - 015-P200834-DA
- woodLED single SPOT mini, 4000K, DALI, maple - 015-M200844-DA
- woodLED single SPOT mini, 4000K, DALI, oak - 015-D200844-DA
- woodLED single SPOT mini, 4000K, DALI, cherry - 015-C200844-DA
- woodLED single SPOT mini, 4000K, DALI, walnut - 015-W200844-DA
- woodLED single SPOT mini, 4000K, DALI, palisander - 015-P200844-DA