

# CEILING LED LUMINAIRE

POWER SUPPLY: 230 V AC / 50 - 60 Hz

LIGHT SOURCE: Samsung 2835 LED

POWER: 123 W

LUMINOUS FLUX: 11130 lm / 4000 K

BEAM ANGLE: 120°

DIMMING: PUSH DIMM / DALI

CRI: 90

PROTECTION: IP20

DIMENSIONS: 850 x 850 x 104 mm

AMBIENT TEMPERATURE: -15 to +40°C

COLOUR TEMPERATURE: 3000 / 4000 K

WEIGHT: 13 kg

MATERIAL: aluminium, wood, steel, PMMA

APPLICATION: interior



## TRILUM


TRILUM - Sladovnicka 28 - 971 01 Trnava - Slovakia  
www.trilum.eu - trilum@trilum.eu - 00421 948 708 008

# DATA SHEET


woodLED SLOPE 900



LIGHT DISTRIBUTION



DIMENSIONS



OPTIONAL VENEERING



ORDER CODES

woodLED SLOPE 900, 3000K, DALI- maple - 008-MM0083S-DA  
woodLED SLOPE 900, 3000K, DALI - oak - 008-DD0083S-DA  
woodLED SLOPE 900, 3000K, DALI - cherry - 008-CC0083S-DA  
woodLED SLOPE 900, 3000K, DALI - walnut - 008-WW0083S-DA  
woodLED SLOPE 900, 3000K, DALI - palisander - 008-PP0083S-DA  
woodLED SLOPE 900, 4000K, DALI - maple - 008-MM0084S-DA  
woodLED SLOPE 900, 4000K, DALI - oak - 008-DD0084S-DA  
woodLED SLOPE 900, 4000K, DALI - cherry - 008-CC0084S-DA  
woodLED SLOPE 900, 4000K, DALI - walnut - 008-WW0084S-DA  
woodLED SLOPE 900, 4000K, DALI - palisander - 008-PP0084S-DA