

CEILING LED LUMINAIRE

POWER SUPPLY: 230 V AC / 50 - 60 Hz

LIGHT SOURCE: Samsung 2835 LED

POWER: 123 W

LUMINOUS FLUX: 11130 lm / 4000 K

BEAM ANGLE: 120°

DIMMING: PUSH DIMM / DALI

CRI: 90

PROTECTION: IP20

DIMENSIONS: Ø 842 x 104 mm

AMBIENT TEMPERATURE: -15 to +40°C

COLOUR TEMPERATURE: 3000 / 4000 K

WEIGHT: 12 kg

MATERIAL: aluminium, wood, steel, PMMA

APPLICATION: interior



TRILUM


TRILUM - Sladovnícka 28 - 971 01 Trnava - Slovakia
www.trilum.eu - trilum@trilum.eu - 00421 948 708 008

DATA SHEET


woodLED SOFT 900



LIGHT DISTRIBUTION



DIMENSIONS



OPTIONAL VENEERING



ORDER CODES

woodLED SOFT 900, 3000K, DALI - maple - 035-MM0083S-DA
woodLED SOFT 900, 3000K, DALI - oak - 035-DD0083S-DA
woodLED SOFT 900, 3000K, DALI - cherry - 035-CC0083S-DA
woodLED SOFT 900, 3000K, DALI - walnut - 035-WW0083S-DA
woodLED SOFT 900, 3000K, DALI - palisander - 035-PP0083S-DA
woodLED SOFT 900, 4000K, DALI - maple - 035-MM0084S-DA
woodLED SOFT 900, 4000K, DALI - oak - 035-DD0084S-DA
woodLED SOFT 900, 4000K, DALI - cherry - 035-CC0084S-DA
woodLED SOFT 900, 4000K, DALI - walnut - 035-WW0084S-DA
woodLED SOFT 900, 4000K, DALI - palisander - 035-PP0084S-DA