

SUSPENSION LED LUMINAIRE

POWER SUPPLY: 230 V AC / 50 - 60 Hz

LIGHT SOURCE: Samsung 2835 LED

POWER: 155 W

LUMINOUS FLUX: 15300 lm / 4000 K

BEAM ANGLE: 120°

DIMMING: PUSH DIMM / DALI

CRI: 90

PROTECTION: IP20

DIMENSIONS: 1110 x 1110 x 104 mm

Rope length max.2000 mm

AMBIENT TEMPERATURE: -15 to +40°C

COLOUR TEMPERATURE: 3000 / 4000 K

WEIGHT: 25 kg

MATERIAL: aluminium, wood, steel, PMMA

APPLICATION: interior



TRILUM


TRILUM - Sladovnicka 28 - 971 01 Trnava - Slovakia
www.trilum.eu - trilum@trilum.eu - 00421 948 708 008

DATA SHEET


woodLED SQUARE Hang 1200



LIGHT DISTRIBUTION



DIMENSIONS



OPTIONAL VENEERING



ORDER CODES

woodLED SQUARE 1200, 3000K, DALI - maple+KIT - 003-MM0H83S-DA + KIT
woodLED SQUARE 1200, 3000K, DALI - oak+KIT - 003-DD0H83S-DA + KIT
woodLED SQUARE 1200, 3000K, DALI - cherry+KIT - 003-CC0H83S-DA + KIT
woodLED SQUARE 1200, 3000K, DALI - walnut +KIT - 003-WW0H83S-DA + KIT
woodLED SQUARE 1200,3000K, DALI - palisander +KIT - 003-PP0H83S-DA + KIT
woodLED SQUARE 1200, 4000K, DALI - maple +KIT - 003-MM0H84S-DA + KIT
woodLED SQUARE 1200, 4000K, DALI - oak +KIT - 003-DD0H84S-DA + KIT
woodLED SQUARE 1200, 4000K, DALI - cherry +KIT - 003-CC0H84S-DA + KIT
woodLED SQUARE 1200, 4000K, DALI - walnut +KIT - 003-WW0H84S-DA + KIT
woodLED SQUARE 1200,4000K, DALI - palisander +KIT - 003-PP0H84S-DA + KIT