

# SUSPENSION LED LUMINAIRE

POWER SUPPLY: 230 V AC / 50 - 60 Hz

LIGHT SOURCE: Samsung 2835 LED

POWER: 55 W

LUMINOUS FLUX: 4860 lm / 4000 K

BEAM ANGLE: 120°

DIMMING: PUSH DIMM / DALI

CRI: 90

PROTECTION: IP20

DIMENSIONS: 590 x 590 x 104 mm

rope lenght max. 2000mm

AMBIENT TEMPERATURE: -15 to +40°C

COLOUR TEMPERATURE: 3000 / 4000 K

WEIGHT: 8 kg

MATERIAL: aluminium, wood, steel, PMMA

APPLICATION: interior



## TRILUM


TRILUM - Sladovnícka 28 - 971 01 Tmava - Slovakia  
www.trilum.eu - trilum@trilum.eu - 00421 948 708 008

# DATA SHEET


woodLED SQUARE Hang 600



LIGHT DISTRIBUTION



DIMENSIONS



OPTIONAL VENEERING



ORDER CODES

woodLED SQUARE 600, 3000K, DALI - maple +KIT - 001-MM0H83S-DA+KIT  
woodLED SQUARE 600, 3000K, DALI - oak +KIT - 001-DD0H83S-DA+ KIT  
woodLED SQUARE 600, 3000K, DALI - cherry +KIT - 001-CC0H83S-DA+ KIT  
woodLED SQUARE 600, 3000K, DALI - walnut +KIT - 001-WW0H83S-DA+ KIT  
woodLED SQUARE 600, 3000K, DALI - palisander +KIT - 001-PP0H83S-DA+ KIT  
woodLED SQUARE 600, 4000K, DALI - maple +KIT - 001-MM0H84S-DA+ KIT  
woodLED SQUARE 600, 4000K, DALI - oak +KIT - 001-DD0H84S-DA+ KIT  
woodLED SQUARE 600, 4000K, DALI -cherry+KIT - 001-CC0H84S-DA+ KIT  
woodLED SQUARE 600, 4000K, DALI - walnut + KIT - 001-WW0H84S-DA+ KIT  
woodLED SQUARE 600, 4000K, DALI - palisander+KIT - 001-PP0H84S-DA+ KIT