

CEILING LED LUMINAIRE

POWER SUPPLY: 230 V AC/ 50 - 60 Hz

LIGHT SOURCE: LED

POWER: 3x8 W

LUMINOUS FLUX: 3x650 Lm

BEAM ANGLE: 40°

DIMMING: Non Dimm / DALI Dimm

CRI: 90

PROTECTION: IP20

DIMENSIONS: 317 x 118 x 135 mm

AMBIENT TEMPERATURE: -15 to +40°C

COLOUR TEMPERATURE: 3000 / 4000 K

MATERIAL: aluminium, wood, steel, PMMA

APPLICATION: interior



TRILUM


TRILUM - Sladovnicka 28 - 971 01 Trnava - Slovakia
www.trilum.eu - trilum@trilum.eu - 00421 948 708 008

DATA SHEET


woodLED tripleSPOT mini



LIGHT DISTRIBUTION



DIMENSIONS



OPTIONAL VENEERING



ORDER CODES

- woodLED triple SPOT mini, 3000K, Non Dimm, maple - 017-M200834-00
- woodLED triple SPOT mini, 3000K, Non Dimm, oak - 017-D200834-00
- woodLED triple SPOT mini, 3000K, Non Dimm, cherry - 017-C200834-00
- woodLED triple SPOT mini, 3000K, Non Dimm, walnut - 017-W200834-00
- woodLED triple SPOT mini, 3000K, Non Dimm, palisander - 017-P200834-00
- woodLED triple SPOT mini, 4000K, Non Dimm, maple - 017-M200844-00
- woodLED triple SPOT mini, 4000K, Non Dimm, oak - 017-D200844-00
- woodLED triple SPOT mini, 4000K, Non Dimm, cherry - 017-C200844-00
- woodLED triple SPOT mini, 4000K, Non Dimm, walnut - 017-W200844-00
- woodLED triple SPOT mini, 4000K, Non Dimm, palisander - 017-P200844-00
- woodLED triple SPOT mini, 3000K, DALI, maple - 017-M200834-DA
- woodLED triple SPOT mini, 3000K, DALI, oak - 017-D200834-DA
- woodLED triple SPOT mini, 3000K, DALI, cherry - 017-C200834-DA
- woodLED triple SPOT mini, 3000K, DALI, walnut - 017-W200834-DA
- woodLED triple SPOT mini, 3000K, DALI, palisander - 017-P200834-DA
- woodLED triple SPOT mini, 4000K, DALI, maple - 017-M200844-DA
- woodLED triple SPOT mini, 4000K, DALI, oak - 017-D200844-DA
- woodLED triple SPOT mini, 4000K, DALI, cherry - 017-C200844-DA
- woodLED triple SPOT mini, 4000K, DALI, walnut - 017-W200844-DA
- woodLED triple SPOT mini, 4000K, DALI, palisander - 017-P200844-DA