

LINEA

wall


EN Luminaire housing and front cover from extruded aluminium profile, angular version; no visible screws; surface powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; HPO (High Performance Opal) cover for uniform illumination; or with specially computed, asymmetrical lens for homogeneous lighting intensity (installation optionally for floor or ceiling illumination); energy-efficient LEDs with very good colour rendering; optionally with switch for the JUST 26 spotlight modules

DE Leuchtenkörper und Frontabdeckung aus Aluminiumstrangpressprofil, kantige Ausführung; keine sichtbaren Schrauben; Oberfläche pulverbeschichtet; geeignet für Wandmontage; homogene Wand- bzw. Deckenaufhellung durch gleichmäßige direkt/indirekte Lichtverteilung; HPO (High Performance Opal) Abdeckung für homogene Ausleuchtung; oder mit speziell berechneter, asymmetrischer Linse für homogene Beleuchtungsstärken (Montage wahlweise zur Boden- oder Deckenaufhellung); energieeffiziente LEDs mit sehr guter Farbwiedergabe; optional mit Schalter für JUST 26 Strahlereinsätze

Quickinfo

3000 K, 4000 K, TW
 CRI ≥ 90, 3 SDCM
 up to 117 lm/W
 L85 @ 50 000 h
 non DIM, DALI-2

Types



Colours




Light distributions



asym./opal/ opal/
 opal opal spot



system
 solution (p.960)



CRI ≥ 98
 XPECTRUM

Order options

COLOUR TEMPERATURE	••
3000K	5
4000K	6
tunable white 2700–5000K*	D

*available from L 610mm | DALI-2 DT8

CONTROL	◆
non DIM*	1
non DIM/ switch (only spotlights)	2
DALI-2*	3
DALI-2/ switch (only spotlights)	4

*not for variants with spotlights

MATERIAL COLOUR	■
○ pure white RAL 9010	7
● jet black RAL 9005	8

SPOTLIGHT ALIGNMENT	▼
left	B
right	C
left and right	





spotlight(s) only with 3000K

Options on request

COLOUR RENDERING INDEX
CRI ≥ 98 XPECTRUM

COLOUR TEMPERATURE
2700K

MATERIAL COLOUR
special colours



LINEA wall



↓ OPAL HIGH PERFORMANCE / ↑ OPAL HIGH PERFORMANCE

SYS. POWER	COLOUR TEMP.	LUMINOUS FLUX	L (mm)	ORDER CODE
14.7 W	3000K	↓ 648/± 648lm	310	058-61711:◆◆AH
	4000K	↓ 715/± 715lm		
29.3 W	3000K	↓ 1300/± 1300lm	610	058-6172:◆◆AH
	4000K	↓ 1430/± 1430lm		
59 W	3000K	↓ 2590/± 2590lm	1210	058-6174:◆◆AH
	4000K	↓ 2860/± 2860lm		
111 W	3000K	↓ 5190/± 5190lm	2410	058-6178:◆◆AH
	4000K	↓ 5720/± 5720lm		



↓ OPAL HIGH PERFORMANCE / ↑ ASYMMETRIC

SYS. POWER	COLOUR TEMP.	LUMINOUS FLUX	L (mm)	ORDER CODE
14.7 W	3000K	↓ 648/± 821lm	310	058-61711:◆◆AA
	4000K	↓ 715/± 906lm		
29.3 W	3000K	↓ 1300/± 1640lm	610	058-6172:◆◆AA
	4000K	↓ 1430/± 1810lm		
59 W	3000K	↓ 2590/± 3280lm	1210	058-6174:◆◆AA
	4000K	↓ 2860/± 3620lm		
111 W	3000K	↓ 5190/± 6570lm	2410	058-6178:◆◆AA
	4000K	↓ 5720/± 7250lm		



↑ OPAL HIGH PERFORMANCE / 1 SPOTLIGHT


SYS. POWER	COLOUR TEMP.	LUMINOUS FLUX	L (mm)	ORDER CODE
29.3 W	3000K	↓ 1300/± 1300lm	710	058-6172:◆◆AH
	4000K	↓ 1430/± 1430lm		
59 W	3000K	↓ 2590/± 2590lm	1310	058-6174:◆◆AH
	4000K	↓ 2860/± 2860lm		
111 W	3000K	↓ 5190/± 5190lm	2510	058-6178:◆◆AH
	4000K	↓ 5720/± 5720lm		




↑ OPAL HIGH PERFORMANCE / 2 SPOTLIGHTS

SYS. POWER	COLOUR TEMP.	LUMINOUS FLUX	L (mm)	ORDER CODE
59 W / 2 x 6 W	3000K	↑ 2590/3280lm	1410	058-6174:◆◆DH
	4000K	↑ 2860/3620lm		
111 W / 2 x 6 W	3000K	↑ 5190/6570lm	2610	058-6178:◆◆DH
	4000K	↑ 5720/7250lm		

Light distributions



↓ opal high performance
↑ opal high performance



↓ opal high performance
↑ asymmetric

LUMINOUS FLUX value calculated for CRI ≥ 90, colour white, cover opal